



US009983162B2

(12) **United States Patent**
Chaum et al.

(10) **Patent No.:** **US 9,983,162 B2**

(45) **Date of Patent:** **May 29, 2018**

(54) **METHOD AND DEVICE FOR DETECTION OF BIOAVAILABLE DRUG CONCENTRATION**

(51) **Int. Cl.**
G01N 27/327 (2006.01)
A61M 5/142 (2006.01)

(Continued)

(71) Applicants: **THE UNIVERSITY OF TENNESSEE RESEARCH FOUNDATION**,
Knoxville, TN (US); **THE UNIVERSITY OF MEMPHIS RESEARCH FOUNDATION**,
Memphis, TN (US)

(52) **U.S. Cl.**
CPC **G01N 27/3275** (2013.01); **A61M 5/142**
(2013.01); **A61M 5/1723** (2013.01); **G01N 27/333** (2013.01); **A61M 2202/048** (2013.01)

(58) **Field of Classification Search**
CPC G01N 27/3275; G01N 27/333; G01N 27/3335

See application file for complete search history.

(72) Inventors: **Edward Chaum**, Memphis, TN (US);
Erno Lindner, Germantown, TN (US);
Jidong Guo, Chungdhun (CN)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,053,381 A 10/1977 Hamblen et al.
4,280,494 A 7/1981 Cosgrove, Jr. et al.
(Continued)

FOREIGN PATENT DOCUMENTS

WO 2006040588 A1 4/2006
WO 2008030582 A2 3/2008
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 259 days.

OTHER PUBLICATIONS

Justin M. Zook, Jan Langmaier, Erno Lindner, Current-polarized ion-selective membranes: The influence of plasticizer and lipophilic background electrolyte on concentration profiles, resistance, and voltage transients, *Sensors and Actuators B: Chemical*, vol. 136, Issue 2, Mar. 2, 2009, pp. 410-418, ISSN 0925-4005, http://dx.doi.org/10.1016/j.snb.*

(Continued)

Primary Examiner — Louis J Rufo

(74) *Attorney, Agent, or Firm* — Baker Donelson

(21) Appl. No.: **14/404,674**

(22) PCT Filed: **Mar. 14, 2013**

(86) PCT No.: **PCT/US2013/031747**

§ 371 (c)(1),

(2) Date: **Dec. 1, 2014**

(87) PCT Pub. No.: **WO2013/180814**

PCT Pub. Date: **Dec. 5, 2013**

(65) **Prior Publication Data**

US 2015/0119848 A1 Apr. 30, 2015

Related U.S. Application Data

(60) Provisional application No. 61/654,469, filed on Jun. 1, 2012.

(57) **ABSTRACT**

The present invention is directed to an electrochemical sensor involving an electrode and a coating that surrounds the electrode, the coating comprising a structural compo-

(Continued)

